

NH-AL State Forest Tract No. 25-08  
Maximum Deet

Vilas County

Town 41 North, Range 6 East

Section 23 – SW¼, S½ NW¼, NENW, NWNE, S½ NE¼, NWSE

Section 22 – SENE

10% of the total sale bid value will be required as bid bond.

15% of the total sale bid value will be required for performance bond.

The cutting area is approximately 196 acres.

The contract period is 2 years.

All trees that will yield one or more 100-inch sticks to the minimum top diameter chosen by the bidder will be cut and utilized the exception of black spruce which yield two or more sticks within Area B.

---

ESTIMATED VOLUME (CORDS)  
MINIMUM TOP DIAMETER

<u>SPECIES</u>	<u>4"</u>	<u>Whole Tree</u>	<u>Advertised Price Per Unit</u>
Mixed Hardwood <sup>1</sup>	1100	1400	\$ 15.90
Aspen	725	900	\$ 17.00
White Birch	500	625	\$ 15.90
Balsam Fir <sup>2</sup>	400	500	\$ 10.00
Oak	260	320	\$ 12.80
Red Pine <sup>3</sup>	38	45	\$ 38.00
Fuelwood <sup>4</sup>	20		\$ 4.30

ESTIMATED VOLUME (MBF)

Oak	50	\$ 187.00
White Birch	40	\$ 124.00
Mixed Hardwood <sup>5</sup>	20	\$ 128.00

**Total Minimum Bid Value \$ 63,493.00**

---

<sup>1</sup> Approximately 71% red maple, 29% sugar maple, <1% ironwood.

<sup>2</sup> Approximately 61% balsam fir, 35% black spruce, 4% white spruce.

<sup>3</sup> Approximately 49% white pine, 32% red pine, 19% scotch pine.

<sup>4</sup> Approximately 35% oak, 65% white birch.

<sup>5</sup> Approximately 62% red maple, 38% sugar maple.

Special Conditions:

1. Cutting must be concurrent for all species to be harvested.(9)
2. Trees may not be felled into wetland/swamp areas.(16)
3. All pine products cut between June 1<sup>st</sup>. and September 1<sup>st</sup>. must be removed from the sale area within three weeks time of cutting. Pine products during the remainder of the year must be removed prior to June 1<sup>st</sup>. of each year.(35)
4. Pole skidding WILL NOT be allowed within marked areas.(9)
5. Cutting within Area A: will only be permitted during extensive dry periods and or frozen ground.
6. Slash along Trout Lake Road must be pulled back at least 25 feet from roads edge concurrently with cutting.(16)